



Subjective Visual Quality Assessment for High-Fidelity Learning-Based Image Compression

Mohsen Jenadeleh, Jon Sneyers, Panqi Jia, Shima Mohammadi, João Ascenso, Dietmar Saupe



05 May 2025

Motivation


- Deep learning-based image compression is emerging as a powerful alternative to traditional codecs, offering superior rate-distortion performance and perceptual quality.
- JPEG AI is a new compression standard that leverages neural networks for high-fidelity image reconstruction.
- However, the artifacts introduced by these methods differ from those in classical codecs and are often misjudged by traditional quality metrics such as PSNR or SSIM.
- Robust subjective quality assessment is essential to properly evaluate and benchmark these advanced compression techniques.

Objectives

- Extend the JPEG AIC-3 IQA dataset* by including JPEG AI compressed images alongside existing codecs: JPEG 1, JPEG 2000, AVIF, JPEG XL, and VVC.
- Evaluate the perceptual quality of JPEG AI through large-scale subjective testing.
- Benchmark the performance of objective image quality metrics on the updated dataset.
- Analyze statistical differences in metric performance to assess reliability.

* Testolina, Michela, Mohsen Jenadeleh, Shima Mohammadi, Shaolin Su, Joao Ascenso, Touradj Ebrahimi, Jon Sneyers, and Dietmar Saupe. "Fine-grained subjective visual quality assessment for high-fidelity compressed images". *The Data Compression Conference (DCC)*, 2025.

Source Images and Crops from JPEG AIC-3 dataset



Top: Full-resolution images.

Bottom: Crops (620×800 px) used in the subjective test..

JPEG AI Encoding Setup

- Each source image was compressed using JPEG AI at 10 distortion levels.
- Bitrates ranged from 0.3 to 1.65 bpp in steps of 0.15 bpp.
- Range visually verified to match the distortion levels of other codecs.
- JPEG AI VM 7.0 used with three highest-rate models.

Command used:

```
python -m src.reco.scripts.eval --cfg ./cfg/tools_on.json  
      ./cfg/oper_point/hop.json ./cfg/BRM/regen_list.json  
      --coding_type enc_dec -target_bpps [BPP*100]
```

- Dataset: 50 JPEG AI images (5 sources $\times$ 10 bitrates).


Subjective Evaluation Framework

- JPEG AIC-3 protocol* using plain (PTC) and boosted triplet (BTC) formats.
- Boosting includes: zoomin and artifact amplification (factor of 2), flicker (10 Hz).
- BTC is evaluated at all 10 bitrates; PTC at 5 bitrates (2, 4, 6, 8, 10).
- For the five source images, the BTC method included a total of 660 triplets, divided into 5 batches of 132 questions each.
- The PTC method consisted of 180 triplets, split into two batches of 90 questions each.
- Crowdsourcing experiment on MTurk using web interfaces of JPEG AIC -3.
- Per-triplet responses: 49 (PTC), 120 (BTC)
- 96,200 triplet comparisons from 459 participants were collected (Participants: 73 (PTC), 386 (BTC)).

**ISO/IEC DIS 29170-3, "Information technology — advanced image coding and evaluation — Part 3: Subjective quality assessment of high-fidelity images", 2025.*

Screening of Subject Responses


- Batch-level screening was performed for quality control using JPEG AIC-3 criteria.
- Responses were evaluated using two indicators:
 - Accuracy: Distortion-weighted proportion of correct responses.
 - Consistency: Agreement between mirrored triplet responses.
- Batches with an average score (accuracy + consistency) below a threshold were excluded.
 - Thresholds: 0.6563 (PTC), 0.6992 (BTC)
 - Excluded Batches: 51 of 98 (PTC), 46 of 600 (BTC)



Accuracy and consistency scores for observer batches in PTC (left) and BTC (right)..

Bitrate–Distortion Analysis

- A perceptual quality scale in JND units was derived using the JPEG AIC-3 reconstruction method.
- A unified model was fitted using maximum likelihood estimation (MLER), using both BTC and PTC triplet responses to estimate an exponential rate–distortion (RD) function.
- RD curves for JPEG AI are shown in red; other codecs (JPEG 1, JPEG 2000, AVIF, JPEG XL, VVC) are shown in gray.
- JPEG AI delivers good perceptual quality at low bitrates.




Distortion in JND units versus bitrate, with 95% confidence intervals..

Objective Metrics Correlation Results

Metric	Overall		Per-source		Per-codec		JPEG AI	
	PLCC	SRCC	PLCC	SRCC	PLCC	SRCC	PLCC	SRCC
PSNR-Y	0.807	0.816	0.883	0.885	0.851	0.832	0.849	0.815
SSIM	0.894	0.905	0.908	0.904	0.936	0.932	<u>0.926</u>	0.904
MS-SSIM	<u>0.931</u>	<u>0.941</u>	0.943	0.942	<u>0.952</u>	<u>0.951</u>	<u>0.927</u>	<u>0.918</u>
PSNR-HVS	0.867	0.877	0.941	<u>0.948</u>	0.882	0.870	0.846	0.813
IW-SSIM	<u>0.950</u>	<u>0.951</u>	<u>0.947</u>	<u>0.947</u>	0.968	0.962	0.919	0.889
NLPD	0.900	0.913	0.927	0.927	0.936	0.935	0.923	<u>0.905</u>
GMSD	0.894	0.903	<u>0.953</u>	<u>0.957</u>	0.903	0.892	0.901	0.874
Butteraugli	0.883	0.897	0.933	0.937	0.908	0.900	0.858	0.842
SSIMULACRA1	0.898	0.908	0.907	0.902	<u>0.955</u>	<u>0.957</u>	<u>0.923</u>	<u>0.904</u>
SSIMULACRA2	0.900	0.913	0.940	0.941	0.926	0.924	0.874	0.841
VMAF	0.882	0.891	0.903	0.900	0.912	0.925	0.855	0.899
VMAF-neg	0.909	0.921	0.940	0.937	0.932	0.936	0.958	0.963
HDR-VDP-2	<u>0.919</u>	<u>0.929</u>	<u>0.944</u>	0.943	0.929	0.919	0.865	0.814
HDR-VDP-3	<u>0.919</u>	<u>0.933</u>	<u>0.948</u>	<u>0.950</u>	<u>0.937</u>	<u>0.939</u>	<u>0.931</u>	<u>0.953</u>
CVVDP	0.960	0.961	0.962	0.962	<u>0.963</u>	<u>0.958</u>	0.880	0.843

Top 5 values are underlined; Best overall is in bold.

Objective Metric Evaluation (subset)



Selected IQA metrics vs. JND values. Logistic curve fits shown per codec.

Statistical Comparison of Metrics

- Meng–Rosenthal–Rubin (MRR) test* evaluates correlation differences.

Null hypothesis: Equal correlation with subjective scores.

$$H_0 : r_{XZ} = r_{YZ}$$

where r_{XZ} and r_{YZ} are correlations of metrics X and Y with the subjective scores Z .

- The test statistic is:

$$Z = (z_1 - z_2) \left(\frac{2(1 - r_{XY})h}{n - 3} \right)^{-0.5}$$

where:

$$z_1 = \tanh^{-1}(r_{XZ}), \quad z_2 = \tanh^{-1}(r_{YZ})$$

$$h = \frac{1 - f \cdot \bar{r}^2}{1 - \bar{r}^2}, \quad f = \frac{1 - r_{XY}}{2(1 - \bar{r}^2)}, \quad \bar{r}^2 = \frac{r_{XZ}^2 + r_{YZ}^2}{2}$$

- We use a two-tailed test with significance level $\alpha = 0.05$ to determine if differences are statistically meaningful.

*Xiao-Li Meng, Robert Rosenthal, and Donald B Rubin, "Comparing correlated correlation coefficients.," *Psychological Bulletin*, vol. 111, no. 1, pp. 172, 1992.

MRR Statistical Test Result

Metric	PSNR-Y	SSIM	MS-SSIM	PSNR-HVS	IW-SSIM	NLPD	GMSD	Butteraugli	SSIMU1	SSIMU2	VMAF	VMAF-neg	HDR-VDP2	HDR-VDP3	CVVDP
PSNR-Y	0	-1	-1	-1	-1	-1	-1	-1	-1	-1	-1	-1	-1	-1	-1
SSIM	+1	0	0	+1	-1	+1	+1	+1	+1	+1	+1	+1	+1	0	-1
MS-SSIM	+1	0	0	+1	-1	+1	+1	+1	+1	+1	+1	+1	+1	+1	-1
PSNR-HVS	+1	-1	-1	0	-1	-1	-1	-1	-1	-1	0	-1	-1	-1	-1
IW-SSIM	+1	+1	+1	+1	0	+1	+1	+1	+1	+1	+1	+1	+1	+1	-1
NLPD	+1	-1	-1	+1	-1	0	0	+1	0	0	+1	0	-1	-1	-1
GMSD	+1	-1	-1	+1	-1	0	0	0	0	0	0	0	-1	-1	-1
Butteraugli	+1	-1	-1	+1	-1	-1	0	0	0	-1	0	-1	-1	-1	-1
SSIMULACRA1	+1	-1	-1	+1	-1	0	0	0	0	0	+1	0	-1	-1	-1
SSIMULACRA2	+1	-1	-1	+1	-1	0	0	+1	0	0	+1	0	-1	-1	-1
VMAF	+1	-1	-1	0	-1	-1	0	0	-1	-1	0	-1	-1	-1	-1
VMAF-neg	+1	-1	-1	+1	-1	0	0	+1	0	0	+1	0	0	-1	-1
HDR-VDP2	+1	-1	-1	+1	-1	+1	+1	+1	+1	+1	+1	0	0	0	-1
HDR-VDP3	+1	0	-1	+1	-1	+1	+1	+1	+1	+1	+1	+1	0	0	-1
CVVDP	+1	+1	+1	+1	+1	+1	+1	+1	+1	+1	+1	+1	+1	+1	0

MRR Test: +1 = row is significantly better; -1 = significantly worse; 0 = no significant difference.

Conclusion

- 15 full-reference IQA metrics evaluated.
- Most metrics overestimate quality for JPEG AI images.
- Best performers overall:
 - CVVDP (highest overall correlation)
 - VMAF-neg (best for JPEG AI specifically)
- JPEG AI delivers good perceptual quality at low bitrates.
- Subjective testing remains essential in high-fidelity ranges.
- Use statistical testing for comparing objective metrics performance.


Resources and Dataset

- **Dataset and code:**

<https://github.com/jpeg-aic/dataset-JPEG-AI-SDR25>

- Includes:

- Source and compressed images
- Triplet responses (plain and boosted)
- JND reconstructions and metric scores
- Statistical analysis scripts



Scan to access dataset and code

Thank you!