

videoparser-ng

An open source, fast and scalable bitstream parser




Werner Robitza, VQEG Meeting Dec. 2025




Agenda

- Video model types, an overview – and P.1204.3
- Existing bitstream parsers, and our new one
- Details and future directions

Pixel-Based Video Quality Models




Bitstream- and Metadata-based Video Quality Models



ITU-T P.1204.3 and Bitstream Parsing

- Bitstream-based models require parsing of different kinds of video sources (containers, codecs)
- Example model that achieves great accuracy comparable to full-reference model: P.1204.3



A Quick History of Bitstream Parsers

- Erana264 (2010?) – Ericsson GUI-based bitstream analyzer, defunct
- Elecard StreamEye – Commercial tool to visualize macroblocks, motion vectors, ...
- VQEG JEG-Hybrid (2010–2012?) – hybrid model development project
 - Development of an H.264 bitstream data format (HMIX) by modifying H.264 encoder
 - Assumed packet loss → less practical relevance now
- VideoParser from P.1203 development
 - Based on FFmpeg and modified decoders



Legacy VideoParser

- Written by Deutsche Telekom in collaboration with TU Berlin/TU Ilmenau for model development during P.1203 phase (P.1203.1 Mode 3 → bitstream model)
 - Worked well during model training and validation
 - Suboptimal speed due to tradeoff between “getting as many metrics as possible” and optimization
 - Code base became unmaintained and could not be compiled on newer systems
 - No AV1 support
- Long-term issues for future developments production deployments



The New *videoparser-ng*

- Free and open source (LGPL-licensed)
- Based on FFmpeg and libaom for extracting bitstream data
- C++ API and CLI interface
- Linux and macOS support, amd64/arm64
- Static binaries for download

Features:

- Clean, streaming JSON format as output
- H.264, HEVC, VP9, AV1
- QP parameters and motion vectors
- Extensible platform with unit tests



```
werner@cerberus-2:~/Documents/Projects/aveq/aveq/cpp/videoparser-ng
videoparser-ng on master on v29.1.2 using default/
→ ./build/VideoParserCli/video-parser test/test-libvpx-vp9.mp4 -n 3 | jq
{
  "type": "sequence_info",
  "video_bit_depth": 8,
  "video_bitrate": 41.0,
  "video_codec": "vp9",
  "video_codec_level": -99,
  "video_codec_profile": 0,
  "video_duration": 10.0,
  "video_frame_count": 300,
  "video_framerate": 30.0,
  "video_height": 240,
  "video_pix_fmt": "yuv420p",
  "video_width": 320
}
{
  "coefs_bit_count": 28119,
  "current_poc": 0,
  "dts": 0.0,
  "frame_idx": 0,
  "frame_type": 1,
  "is_idr": true,
  "mb_mv_count": 0,
}
```

<https://github.com/aveq-research/videoparser-ng>



Bitstream Data and Speed Comparisons

Type	Metrics
QP	Avg., min, max, std. deviation
Motion vectors	Avg. MV length, std. deviation, avg. X and Y components, motion vector residuals
Macroblock stats	Blocks with MVs, explicitly coded MVs, Bit count for motion and transform coeffs
Metadata	Frame type, codec, bitrate, width/height, profile, ...


Speed improvement examples:

- 16x speedup for 1080p HEVC
- 70x speedup for 2160p H.264

(M1 Mac, comparing old amd64 VideoParser against arm64 videoparser-ng)

How it Works

- Modified FFmpeg (libavcodec) 8.0 to extract the data
- Modified libaom (because FFmpeg has no built-in AV1 decoder)
- Lightweight C++ library to pass data from Ffmpeg
- CLI to output data in structured format



Feature Engineering on the Raw Stats

- Raw bitstream statistics cannot be directly used for quality estimation
 - Feature engineering based on per-GOP or per-segment statistics
 - E.g. as in the P.1204.3 case, feature engineering done by Rakesh Rao and Steve Göring during model development/training process
- The aggregation is up to the consumer of the raw statistics.

Aggregated Feature	Type
Framerate	float
Resolution ($width \times height$) of the distorted video	int
Codec (H.264, H.264_10bit, H.265, H.265_10bit, VP9)	boolean
$Q_{parametric}$	float
Mean bitrate per segments	float
Maximum frame size	int
Kurtosis of the non-I frame sizes	float
Standard deviation of frame size of non-I frame in bits	float
Quant ($Quant = \frac{QP_{non-I frames}}{QP_{max}}$)	float
IQR of the average QP of non-I frames	float
IQR of the minimum QP per frame	float
Kurtosis of the average QP of non-I frames	float
Mean of the average QP of non-I frames	float
Standard deviation of maximum QP of non-I frames	float
Kurtosis of the average motion per frame over all frames in a segment	float
Minimum standard deviation of motion in the x-direction (horizontal motion) per frame	float

From: Raake et al., Multi-Model Standard for Bitstream-, Pixel-Based and Hybrid Video Quality Assessment of UHD/4K: ITU-T P.1204, IEEE Access (2020)

Future Directions

Legacy Mode for P.1204.3

- The “old” video parser had some normalizations built-in, i.e., feature engineering at the extraction level
- The new videoparser-ng does not do that, but it has a “legacy” mode to emulate it (because P.1204.3 was trained that way). Currently WIP.

Metric	New Implementation	Old Implementation	Difference
per_sequence	4.118	4.087	+0.031
baseline_mos	4.165	4.163	+0.002
rf_pred	4.071	4.011	+0.060
bitrate	6446.1	6621.5	-175.4
quant	0.6402	0.6407	-0.0005
mean_qp_non_i	32.65	32.67	-0.02

→ Used for reimplementing P.1204.3 (validation ongoing)

More Metrics

- Provide in-depth statistics e.g. on MB types, CU sizes, ... based on compile-time flags
- Black border detection for QP values

Extending Codec Support

- Adding VVC support
- Retraining of P.1203.1 for AV1

Thank You!

The original VideoParser:

- **Peter List** (Deutsche Telekom) for the initial code
- **Steve Göring, Rakesh Rao Ramachandra Rao, Anton Schubert (TU Ilmenau)** for troubleshooting builds and adding features

The new videoparser-ng:

- **Jonatan Stenlund** (Ericsson, Luleå University of Technology) for implementing initial motion vector support for HEVC
- **Bob Forsman** (Ericsson) for providing bug reports and API suggestions



Contact us



Werner Robitza
CEO

werner.robirtza@aveq.info
<https://aveq.info>